

Claims

1. A Viterbi decoder including an Add-Compare-Select unit having a butterfly unit (300) comprising:
 - 5 first adder means (310) for receiving a first path metric and a branch metric and for producing at its output the addition thereof;
 - 10 second adder means (320) for receiving a second path metric and said branch metric and for producing at its output the addition thereof;
 - 15 first comparator means (330) coupled to receive the output of the second adder means and coupled to receive the first path metric for comparing therebetween;
 - 20 second comparator means (340) coupled to receive the output of the first adder means and coupled to receive the first path metric for comparing therebetween;
 - 25 first selection means (350) for selecting between the second adder means output and the first path metric to produce a first survivor path metric in dependence on the first comparator means comparison; and
 - 30 second selection means (360) for selecting between the first adder means output and the second path metric signal to produce a second survivor path metric in dependence on the second comparator means comparison,

2. The Viterbi decoder of claim 1 wherein the Add-Compare-Select unit further comprises a butterfly unit (300) having:

5 first, second, third and fourth adder means for receiving a first metric, a second metric, a first branch metric and a second branch metric;

10 first comparison means for comparing outputs of the first and second adder means;

15 second comparison means for comparing outputs of the third and fourth adder means;

20 first selection means for selecting between the outputs of the first and second adder means in dependence on the comparison of the first comparison means to produce a first survivor path metric; and

25 second selection means for selecting between the outputs of the third and fourth adder means in dependence on the comparison of the first comparison means to produce a second survivor path metric.

3. The Viterbi decoder of claim 1 adapted for code rates of the type $R = k/m$, where $k > 1$, and k and m are integers.

4. A method of producing metrics for use in a Viterbi decoder comprising selecting metrics such that for at least some trellis transitions a branch metric is zero, whereby a simplified Add-Compare-Select butterfly unit may be used.

5

5. The method of claim 4 wherein the metrics are selected by subtracting from each of a predetermined set of metrics a chosen one thereof to produce a resultant set of metrics having at least one zero value.

10 6. The method of claim 4 further comprising re-adjusting the dynamic range of the selected metrics by multiplying each of the selected metrics by a scaling factor if the following property is satisfied:

$$m_a(\text{bit} = 0) = -m_a(\text{bit} = 1) \forall a$$

15 7. The method of claim 6 adapted for OFDM coding.

8. The method of claim 6 further comprising adapting the selected metrics to additive noise.

20 9. The method of claim 7 wherein the additive noise comprises coloured
noise.

10. The method of claim 4 adapted for code rates of the type $R = k/m$, where $k > 1$, and k and m are integers.

25

